

Milestone Review Flysheet 2021-2022

Institution Boy Scout Troop 17

Milestone PDR

Vehicle Properties	
Total Length (in)	85.4
Diameter (in)	4
Gross Lift Off Weigh (lb)	16.2
Airframe Material(s)	G12 Fiberglass
Fin Material and Thickness (in)	G10 Fiberglass 0.125
Coupler Length(s)/Shoulder Length(s) (in)	8"/4"

Motor Properties	
Motor Brand/Designation	Aerotech K805
Max/Average Thrust (lb)	213/180
Total Impulse (lbf-s)	396
Mass Before/After Burn (lb)	3.4/1.9
Liftoff Thrust (lb)	179
Motor Retention Method	Aeropack

Stability Analysis	
Center of Pressure (in. from nose)	66.1
Center of Gravity (in. from nose)	52
Static Stability Margin (on pad)	3.53
Static Stability Margin (at rail exit)	2.4
Thrust-to-Weight Ratio	11.2:1
Rail Size/Type and Length (in)	1010 /120
Rail Exit Velocity (ft/s)	78.1

Ascent Analysis	
Maximum Velocity (ft/s)	710
Maximum Mach Number	0.63
Maximum Acceleration (ft/s ²)	364
Target Apogee (ft)	5200
Predicted Apogee (From Sim.) (ft)	5345

Recovery System Properties - Overall	
Total Descent Time (s)	77
Total Drift in 20 mph winds (ft)	1954

Recovery System Properties - Energetics		
Ejection System Energetics (ex. Black Powder)		
Energetics Mass - Drogue Chute (grams)	Primary	1.5
	Backup	2
Energetics Mass - Main Chute (grams)	Primary	2
	Backup	3
Energetics Mass - Other (grams) - If Applicable	Primary	
	Backup	

Recovery System Properties - Recovery Electronics	
Primary Altimeter Make/Model	Marsa33
Secondary Altimeter Make/Model	Missile Works RRC3
Other Altimeters (if applicable)	
Rocket Locator (Make/Model)	Missile Works RTX
Additional Locators (if applicable)	
Transmitting Frequencies (all - vehicle and payload)	***Required by CDR*** (Complete on pages 3 and 4)
Describe Redundancy Plan (batteries, switches, etc.)	Each altimeter will have its own screw switch, battery and redundant deployment charges
Pad Stay Time (Launch Configuration)	3 hours

Recovery System Properties - Drogue Parachute				
Manufacturer/Model		Sky Angle Classic		
Size or Diameter (in or ft)		20"		
Main Altimeter Deployment Setting		Apogee		
Backup Altimeter Deployment Setting		Apogee plus 1 sec		
Velocity at Deployment (ft/s)		5		
Terminal Velocity (ft/s)		98.6		
Recovery Harness Material, Size, and Type (examples - 1/2 in. tubular Nylon or 1 in. flat Kevlar strap)		1/4" Tublar Kevlar		
Recovery Harness Length (ft)				
Harness/Airframe Interfaces		1/4-20 1" u-bolt /0.188 fiber glass lid / 1/4" oval quick link / 3 2-56 plastic bolt shear pins		
Kinetic Energy of Each Section (Ft-lbs)	Section 1	Section 2	Section 3	Section 4
	1213	1276		

Recovery System Properties - Main Parachute				
Manufacturer/Model		Sky Angle Classic		
Size or Diameter (in or ft)		60 in		
Main Altimeter Deployment Setting (ft)		750		
Backup Altimeter Deployment Setting (ft)		500		
Velocity at Deployment (ft/s)		98.6		
Terminal Velocity (ft/s)		18.7		
Recovery Harness Material, Size, and Type (examples - 1/2 in. tubular Nylon or 1 in. flat Kevlar strap)		1/4" tublar Kevlar		
Recovery Harness Length (ft)		25		
Harness/Airframe Interfaces		1/4-20 1" u-bolt /0.188 fiber glass lid / 1/4" oval quick link / 3 2-56 plastic bolt shear pins		
Kinetic Energy of Each Section (Ft-lbs)	Section 1	Section 2	Section 3	Section 4
	24.6	6.7	30.3	

Institution Boy Scout Troop 17

Milestone PDR

Payload

Payload 1 (official payload)	Overview
	Three-axis accelerometer connected to dedicated Raspberry Pi Pico data logging computer and MicroSD non-volatile storage device. The payload will log vibrations throughout the flight so that ground analysis of magnitude and frequency can be made.
Payload 2 (non-scored payload)	Overview

Test Plans, Status, and Results

Ejection Charge Tests	A commercially available charge size calculator will be used to estimate the initial size of the charges. This will be the starting point and will be adjusted until a clean section separation is observed. The charge sizes will be documented in the check list and written on the back of each of the ebay lids for future reference.
Sub-scale Test Flights	
Vehicle Demonstration Flights	
Payload Demonstration Flights	

Institution Boy Scout Troop 17

Milestone PDR

Transmitter #1			
Location of transmitter:	Nose cone		
Purpose of transmitter:	GPS tracker		
Brand	Missile Works	250mW	
Model	RTX	902-908 MHz	
Handshake or frequency hopping? (explain)	900 MHz ISM radio band (902-928 MHz). Radio Network Addressing is XBee Pro 900HP Preamble ID: 5. XBee Pro 900HP Network ID's: 0 thru FFFF which are assigned and maintained by the manufacture.		
Distance to closest e-match or altimeter (in)	40" from the Altimeters and 80" from the motor/ematch		
Description of shielding plan:	None is required		

Transmitter #2			
Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Transmitter #3			
Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Transmitter #4			
Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Milestone Review Flysheet 2021-2022

Institution Boy Scout Troop 17

Milestone PDR

Transmitter #5

Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Transmitter #6

Location of transmitter:			
Purpose of transmitter:			
Brand		RF Output Power (mW)	
Model		Specific Frequency used by team (MHz)	
Handshake or frequency hopping? (explain)			
Distance to closest e-match or altimeter (in)			
Description of shielding plan:			

Additional Comments